










## TECHNICAL INFORMATION / TEKNISK INFORMATION



# BERGO NAVY

Material:			Environmentally friendly recyclable UV-stabilized polypropylene. / Miljövänlig återvinningsbar UV-stabiliserad polypropen.
Size of tile: /Plattans storlek:		EN427	301,8 x 301,8 mm. 1 m <sup>2</sup> / box = 11 tiles. 5 m <sup>2</sup> / box = 55 tiles.
Thickness of tile: /Plattans tjocklek:		EN428	13,2 mm.
Weight: /Vikt:		EN430	1 tile: 0,318 kg. 1 m <sup>2</sup> : 3,498 kg.
Point load: /Punktbelastning:		QUALIFIED TEST BY BERGO	400 ton / 1 m <sup>2</sup> = 4000 kg/dm <sup>2</sup>
Light fastness: /Ljusbeständighet:		EN 14836 (>3) ISO 105-B02 (1-8)	4-5 7-8
Weather Fastness /UV- Florida test (1-5):		ASTM D1435 ASTM G154 Cycle A	4/5
Slip resistance: /Halkmotstånd:		SSEN-13893	>0,4
CE certification:		EN 14041	0402-CPD-P605080A




By normal use and treatment the material guarantee time is 5 years.



Bergo Flooring AB fulfills the requirements of ISO 9001.



Bergo Floors are 100% recyclable.



The Bergo Tile - Polypropylene floor covering for use out- and indoors. Reaction to fire Class EfL. Slipperiness DS.



SYSTEM  
1

[www.bergoflooring.com](http://www.bergoflooring.com)

