


TECHNICAL INFORMATION / TEKNISK INFORMATION



BERGO ECO TENNIS

100% recycled composite

Material:		ISO2076	Recycled environmentally-friendly UV-stabilized pp-composite (polypropylene)	/ Miljövämlig återvinningsbar UV-stabiliserad pp-composit (polypropren).
Size of tile: /Plattans storlek:		EN427	301,6 x 301,6 mm. 1 m ² / box = 11 tiles. 5 m ² / box = 55 tiles. 1,09 m ² /sheet = 4x3 tiles.	
Thickness of tile: /Plattans tjocklek:		EN428	13,3 mm.	
Weight: /Vikt:		EN430	1 tile: 0,3 kg. 5 m ² : 17,1 kg (Maxi-pack) 4x3 tiles: 3,6 kg (Preassembled sheets)	
Point load: /Punktbelastning:		QUALIFIED TEST BY BERGO	550 ton / 1 m ² = 5500 kg/dm ²	
Light fastness: /Ljusbeständighet:		EN 14836 (>3) ISO 105-B02 (1-8) ISO 105-A02 (>0,3)	4-5 7-8 4/5	
Weather Fastness /UV-Floorida test (1-5):		ASTM D1435 ASTM G154 Cycle A	4/5	
Slip resistance: /Halkmotstånd:		SSEN-13893 EN13036-4	>0,3 96 PTV	
Impact resistance: /Slagtållighet:		ISO179/1eA ASTM D746	+23 °C = 20 kJ/m ² / -20 °C = 5 kJ/m ² C 15 kJ/m ²	
Fire category /Brandklassning:		EN ISO 11925-2	E _{fl}	
CE certification:		EN 14041	0402-CPD-P605080A	
Shock absorption: /Stötupptagning		EN 14808	6 %	
Vertical deformation: /Svikt		EN 14809	0,3 mm	
Vertical ball behaviour: /Bollstuds		EN 12235	102 %	
Resistance to wear: /Nötningsmotstånd		EN ISO 5470-1	0,1 g / 1000 cycles	
Water infiltration rate: /Vattengenomsläpplighet		EN 12616	Requirement very well achieved. /Uppfyller kraven med god marginal.	
Court pace Classification: /Hastighetsklassificering		ITF CS/01/02-13-600	Medium-fast.	

Packaging:	Quantity / packaging unit:	Quantity / pallet:	Size of pallet:
Maxi-pack carton	5 m ² = 55 tiles	1 pallet = 36 cartons = 180 m ²	1,30 x 0,98 x 2,40 m = 3,06 m ³ , 626 kg gross weight
Preassembled sections	1 section = 4 x 3 tiles = 1,1 m ²	1 pallet = 75 sections = 81,8 m ²	1,26 x 0,96 x 1,15 m = 1,39 m ³ , 283 kg gross weight

EXPLANATION OF EXPANSION IN VARIOUS TEMPERATURES/FÖRKLARING TILL UTVIDGNING I OLIKA TEMPERATURER				
Formula for the size of the expansion: (0,0015 x length of the floor) x (number of increased degrees /10) / Formel för själva expansionens (utvidgnings) storlek: (0,0015 x längden av golvet) x (temperaturökning (i grader)/10)			Expansion: 0,015 % per 10 °C	
Formula for the length of the floor after the expansion: Earlier length + Length of the expansion				
Example Exempel	Length of floor Längd på golvet	Calculation Uträkning	Expansion	Length of floor after expansion Längd på golvet efter expansion
0°C-10°C	10 m	0,0015 x 10 m = 0,015 0,015m x (10°/10) = 0,015	1,5 cm	10,015 m
0°C-30°C	10 m	0,0015 x 10 m = 0,015 0,015m x (30°/10) = 0,045	4,5 cm	10,045 m
20°C-40°C	20 m	0,0015 x 20 m = 0,030 0,030m x (20°/10) = 0,06	6,0 cm	20,06 m




By normal use and treatment the material guarantee time is 10 years.



Bergo Flooring AB fulfills the requirements of ISO 9001.



Bergo Floors are 100% recyclable.



The Bergo Tile - Polypropylene floor covering for use out- and indoors. Reaction to fire Class Efl. Slipperiness DS.



SYSTEM 1



www.bergoflooring.com